

## HS-773TXDG2



Half-Size PCI Slot-CPU-Card, Intel® QM67, Socket G2 (rPGA988B), 2x DDR3 SO-DIMM (max.16GB), 8x USB, 4x COM, 2x LAN, 1x VGA, 1x LVDS (24-bit dual channel), 2x Mini PCIe, 4x SATA, 8-bit DIO

Commell

### System

CPU Socket	Intel® - rPGA988B
CPU	Intel® - Core™ i7 / i5 / i3
	Intel® - Celeron®
Chipsatz	Intel® - QM67
Watchdogtimer	1~255 levels reset
Netzwerk Chipsatz	Intel® - 82574L
max. Netzwerkgeschwindigkeit 1000 Mbit	

### Schnittstelle Rückseite

PS/2	1
DVI	1
RJ45	2

## Onboard Schnittstellen

USB	8
RS 232	5
RS 232/422/485	1
VGA	1
LVDS in bit	24
Audio Out	1
SATA	4
SD Card Socket	1

## Audio

Chipsatz	Realtek® - ALC888
----------	-------------------

## Betriebsbedingungen

Breite	185 mm
Tiefe	122 mm
min. Betriebstemperatur	0 °C
max. Betriebstemperatur	60 °C
Eingangsspannung	DC 5Vsb Requirement, + 5 V, +12 V

## Grafik

Chipsatz	Intel® Core™ integrated HD Graphics Technology
----------	---

## Slots

mini PCI Express	2
------------------	---

Mechanical Drawing

